

Stabilizers Drilling Tools

Features

- Non-Magnetic and AISI 4145 H-MOD 30-36RC material, String and Nearbit
- Can be supplied with Hunting's own proprietary wear resistant hard facing
- All our equipment is manufactured to NS-1™
- Support any NS-2™, DS1 cat 3-5 and API operations
- Large inventory

Benefits

- Bespoke manufacturing to suit customer specific requirements
- 1st rental company worldwide to receive NS-1™ Facility Approval for drilling products
- Our proprietary wear resistant hardfacing is designed to reduce the risk of redress and long term rental
- Fast response times

Stabilizers prevent differential sticking of the drill string by stabilizing the BHA and keeping drill collars and drill pipe away from the borehole wall.

This reduces vibration, drillpipe whirl, and wellbore tortuosity; moreover, the stabilization maintains drilling trajectory whether drilling straight, horizontal, or directional wells.

All our equipment is manufactured to NS-1™ and can support any NS-2™, DS1 cat 3-5 and API operations. Ongoing investment in new equipment enables HEMS to provide rental equipment that is in immaculate order and within spec.

Hunting Stabilizers are manufactured from Non-Magnetic and AISI 4145 H-MOD 30-36RC material, String and Nearbit. All have integral 3 right hand spiral blades, with 210 degree wrap.

→ For technical information see overleaf.



Stabilizers

Technical Information

Standard Integral Blade Stabilizer Specifications

Nominal Gauge (in)	Body O.D. (in)	Body I.D. (in)	Min NS2 bevel Dia. (in)	Min DS1 Cat 3-5 bevel Dia. (in)	Blade Length (in)	Connections
5 3/4" - 6 1/4"	4 3/4"	2 1/4"	4 5/8"	4 39/64"	16"	NC38
8" - 8 1/2"	6 3/4"	2 13/16"	6 21/64"	6 21/64"	19"	NC50
11 3/4" - 12 1/4"	8 1/4"	2 13/16"	7 5/32"	7 10/64"	33"	6 5/8" Reg
11 3/4" - 12 1/4"	9 1/2"	3"	8 51/64"	8 31/64"	33"	7 5/8" Reg
17" - 17 1/2"	9 1/2"	3"	8 51/64"	8 31/64"	33"	7 5/8" Reg
25 3/4" - 26"	9 1/2"	3"	8 51/64"	8 31/64"	33"	7 5/8" Reg